

(12) United States Patent

Umezawa et al.

(10) Patent No.:

US 6,289,182 B1

(45) Date of Patent:

Sep. 11, 2001

METHOD AND APPARATUS FOR DISCRIMINATING TONER BOTTLE TYPES, STIRRING TONER, AND DETECTING THE AMOUNT OF REMAINING TONER

(75) Inventors: Noriyuki Umezawa, Yokohama;

Takayuki Nishi, Fujisawa, both of (JP)

Assignee: Toshiba Tec Kabushiki Kaisha, Tokyo

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/506,370

(22)Filed: Feb. 18, 2000

Int. Cl.⁷ G03G 15/00; G03G 15/08 (51)

(52)

(58)Field of Search 399/12, 27, 258, 399/262

(56)References Cited

U.S. PATENT DOCUMENTS

3,669,072 *	6/1972	Reynolds et al 399/254
4,963,939 *	10/1990	Kurando et al 399/12
4,978,995 *	12/1990	Takahashi 399/12
5,208,637 *	5/1993	Landa 399/120

5,761,566 * 6/1998 Suzuki et al. 399/12 6,075,963 * 6/2000 Ishikawa et al. 399/262

FOREIGN PATENT DOCUMENTS

6-149051 5/1994 (JP).

* cited by examiner

Primary Examiner-Fred L Braun (74) Attorney, Agent, or Firm-Foley & Lardner

ABSTRACT

A method and apparatus for discriminating bottle types, for stirring the toner, and for detecting the amount of toner remaining in the toner bottle. A toner bottle is adapted to fit the apparatus for discriminating toner bottle types, and a toner bottle is adapted for the apparatus for stirring toner. The genuineness of the toner bottle product is checked by sensing a rib assumed to be formed with a predetermined length on the outer surface of the toner bottle. Toner is stirred by continuously rotating the toner bottle in forward and reverse directions. The toner bottle can be easily rotated in the forward and reverse directions by sensing the rib of the toner bottle by using the sensor. Since the load of rotation of the toner bottle changes in accordance with the amount of remaining toner, the rotational speed of the toner bottle is sensed by using the sensor to check whether toner is close to empty.

13 Claims, 8 Drawing Sheets



